

Facestock

A bi-axially oriented, glossy bright metallised polypropylene film with a print-receptive top coating.

Basis Weight	41 g/m ²	ISO 536
Caliper	47 µm	ISO 534

Adhesive

S692N is a general-purpose permanent, emulsion acrylic adhesive.

Liner

A clear rPET liner exhibiting optimum smoothness of the adhesive layer. Designed to provide high strength and uniform quality, permitting very high speed conversion and dispensing with reliability in severe application environments. rPET liner contains 30% recycled content and it is 100% recyclable.

Basis Weight	43 g/m ²	ISO	536
Caliper	30 µm	ISO 534	

Laminate

Total Caliper	88 µm ± 10%	Calculated
---------------	-------------	------------

Typical Performance Data

Initial Tack	10.0 N/25mm	FTM 9 glass
Peel Adhes. 90°	8.0 N/25mm	FTM 2 st.st.
Min. appl. temp.	5°C	
Service temp.	-20°C to 80°C subject to facestock limitations	

**Typical Performance Data only serves as reference to product performance under specified testing conditions and does not represent a product specification. Customers are recommended to test under actual conditions of use to determine its suitability.*

Applications and Use

Applications are predominantly in market segments where rigid containers are used. This product is suitable for labelling of quality products such as cosmetics, toiletries, luxury articles, promotional labeling, automotive lubricants and household chemicals where durability and resistance to moisture or chemicals are required. Product can be used as a cost effective alternative to metallic foil blocking. Due to fairly rigid nature of polypropylene, care should be taken with the use on 'non-uniform' surfaces or where a high level of squeezability is desired.



Conversion/Printing

The modified acrylic based topcoating allows printing by the usual printing technologies including letterpress, flexo, gravure and screen printing, giving good results with solvent, UV curing and water based inks. In case solvent screen inks are used, please consult your ink manufacture. Material shows excellent register stability on press and excellent flat bed conversion while rotary and magnetic dies need additional care. Square corners should be avoided.

Note: The information in this datasheet is correct at time of publishing. Avery Dennison reserves the right to revise the content as required without prior notice.

BW0273A

Fasson® PP TC Silver Elite/S692N/ rPET30N



Food Industry Labels

The adhesive complies with FDA regulations (section 175.105) for indirect food contact.

Statement of Practical Use

As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Shelf life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50% RH). Prolonged storage outside these conditions might reduce the shelf life.

Thailand Malaysia Indonesia Vietnam Myanmar Singapore Philippines

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.