

Facestock

A White, uncoated matt 100% Cotton paper with a Unique 'Velvet finish' appearance. Wet strength and fungicidal treatments.

Basis Weight 120 g/m² ISO 536

Caliper 220 µm ISO 534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

BG45 white, a supercalendered glassine paper.

Basis Weight 72 g/m² ISO 536

Caliper 61 µm ISO 534

Transparency 50 % DIN 53147

Laminate

Total Caliper 305 µm±10% ISO 534

Performance data

Initial Tack 20 N/25mm FTM 9 Glass

Peel Adhesion 90° 7 N/25mm FTM 2 St.St.

Min. Application Temp. 5 °C

Service temperature -20°C to 80°C

Adhesive Performance

The adhesive features high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates. Specially designed for wine labelling applications it allows easy conversion of difficult label shapes.

Applications and use

This product is designed for Wine labelling, it is suitable for primary labelling of high and premium goods eg: spirits, specialist foods. Due to its high stiffness it is not recommended for labelling on small diameters, neck labels in particular. It is important to apply adequate pressure during the labelling process to ensure a good adhesion performance on the substrate.

Conversion & printing

Printable by Offset, Screen, Hot Foil.

Special Approvals

The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry, non fatty foodstuffs.


Shelf life

Two years under storage conditions as defined by FINAT (20-25°C; 40-50%RH)

AD871

Fasson®

COTTON WHITE - S2030 INC-
BG45WH



COTTON WHITE

S2030

BG45WH

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based



©2016 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other



Inspired Brands.
Intelligent World.™

on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.