



Stockman Paper Data Sheet

Silver Metalised PP PP32 WG62

FACE SHEET

Silver Metalised PP

Typical Specifications

Weight	45 ± 2	m ² /kg	MTM 1
Caliper	50 ± 1	um	MTM 1
Gloss	85 ± 5	%	ASTM D245745
Tensile Strength MD	170	N/mm ²	DIN 53455
Tensile Strength CD	200	N/mm ²	DIN 53455

ROLL SIZES

Roll Widths and Lengths converted locally to customer specifications as required.

APPLICATIONS

Suitable for a wide range of promotional and industrial label applications that require weather resistance for extended periods of time.

ADHESIVE

PP32 Permanent Acrylic

Typical Specifications

Weight	22 ± 2	g/m ²	
Initial Tac	10.5 N	FTM 9	
Loop Tac	15N	FTM 9	
90° peel	6.5 (FTM 1) Tear		
Labeling Temp	+5	°C	
Working Temp	-40 ~ +90	°C	
Characteristic	Film Grade general purpose permanent acrylic adhesive. Excellent ageing resistance featuring good tack to low surface energy substrates.		

STORAGE

One Year when stored at 20°C at 50% RH. As with all pressure sensitive materials, we recommend testing for the specific application prior to use.

LINER

WG62

Typical Specifications

Weight	60 ± 3	g/m ²	ISO 536
Caliper	55 ± 5	um	ISO 534
Transparency	49 ± 3	%	DIN 53147
Characteristic	Super calendared glassine liner. Primarily used for roll to roll label conversions and photoelectric detection labeling systems.		